

SunClean™ Downlight

Intelligent, Automatic Disinfection, Air-Cleaning, and Lighting 3-in-1.



LED Downlight
2.5" LED Downlight
3" LED Downlight
4" LED Downlight
5" LED Downlight
6"

[Upgrade to](#) [Upgrade to](#) [Upgrade to](#) [Upgrade to](#) [Upgrade to](#)



2.5" Size: Ø89mm 3" Size: Ø110mm 4" Size: Ø149mm
(Entry-level) 5" Size: Ø174mm
(Entry-level) 6" Size: Ø184mm
(Entry-level)



Radar



Kills up to 99.9%
of all Germs



Military-grade radar
sensor ensures safe use

	2.5" Size: Ø89mm	3" Size: Ø110mm	4" Size: Ø149mm (Entry-level)	5" Size: Ø174mm (Entry-level)	6" Size: Ø184mm (Entry-level)
Lighting Specifications					
Power	5W	7W	11W	11W	13W
Luminous flux	>500 lm	>600 lm	>860 lm	>880 lm	>1040 lm
CCT	3000K/4000K/ 5000K/6000K	3000K/4000K/ 5000K/6000K	3000K/4000K/ 5000K/6000K	3000K/4000K/ 5000K/6000K	3000K/4000K/ 5000K/6000K
Color Temperature Adjustable	NO	NO	NO	NO	NO
CRI	>80	>80	>80	>80	>80
Lamp Lifespan	>15,000 hrs				
UV Specifications					
Diode Type	UV-C LED				
Power	6W	7W	9W	9W	11W
UV Energy	60mW	70mW	90mW	90mW	110mW
Disinfection Area	2 x 2m (4m²)				
Disinfection Modes	30-min automatic mode 3-hour intensive mode				
Detection Sensor	5.8G	5.8G	5.8G	5.8G	5.8G
Beam Radius	90°	90°	90°	90°	90°
Wavelength	260-285nm	260-285nm	260-285nm	260-285nm	260-285nm
Lamp Lifespan	>5000 hrs				
Electrical Specifications					
Voltage	100-240Vac 50/60Hz				
Operation Modes	Manual switch mode / radar sensor automatic mode				
Physical Specifications					
Body	Plastic	Plastic	Plastic	Plastic	Plastic
Body Color	White	White	White	White	White
Dimension	Ø89x51.4mm	Ø110x51.4mm	Ø149x56.5mm	Ø174x59mm	Ø184x59mm
Cut out	Ø70-80mm	Ø90-100mm	Ø130-140mm	Ø155-165mm	Ø165-175mm
Weight	125g	150g	220g	275g	290g
Operating Temperature	-10°C-40°C	-10°C-40°C	-10°C-40°C	-10°C-40°C	-10°C-40°C
Certifications and Warranty					
Certifications	FCC, CE				
Warranty	1 Year				